

## Job Quotation Submittal

Company Name and Contact	<input type="text"/>				
Address, Phone, Fax	<input type="text"/>				
Job Name	<input type="text"/>				
Contractor or Distributor	<input type="text"/>				
Job Classification	<input type="checkbox"/> Commercial	<input type="checkbox"/> Multi-family	<input type="checkbox"/> Single Family		
Required hourly rating	<input type="checkbox"/> 1	<input type="checkbox"/> 2	<input type="checkbox"/> 3	<input type="checkbox"/> 4	
Assembly being penetrated	<input type="checkbox"/> Wood Floor/Ceiling	<input type="checkbox"/> Gypsum Wall	<input type="checkbox"/> Concrete Floor/Wall		
Penetrants	<b>Non metallic wires/cables</b>	<b>Metallic Piping, tubing, conduit</b>	<b>Plastic Pipes</b>	<b>HVAC Ducts</b>	<b>Head of Wall</b>
	Size Range: <input type="text"/>	Size Range: <input type="text"/>	Size Range: <input type="text"/>	Size Range: <input type="text"/>	Size Range: <input type="text"/>

### Firestopping Products:

**Size:**

**Qty:**

Firestop-814+ Intumescent Firestopping Sealant – ASTM-E814/UL 1479	10.3 oz tube	28 oz tube	5 Gal. Pail	<input type="text"/>
Flame Guard-814 Non-Intumescent Firestopping Sealant – ASTM-E814/UL 1479	10.3 oz tube	28 oz tube	5 Gal. Pail	<input type="text"/>
Intumescent Firestopping Collars	3"	4"	6"	<input type="text"/>
7" x 7" x 1/8" Fire Rated Putty Pads - 20 pads/ case				<input type="text"/>
18 Cu. In. Fire Rated Putty Sticks – 12 sticks/ case				<input type="text"/>
2" x 4" x 8" Intumescent Pillows – 25 pillows/ case				<input type="text"/>
Fire Rated Spray Mastic – 5 gallon pail				<input type="text"/>
Other – Mineral Wool, Mortar, - _____				<input type="text"/>

### Additional Products:

**Qty:**

Fire Seal – 136 - ASTM-E136 Rated Caulk For Single Family	<input type="text"/>
100% Construction Silicone – Clear, White, Aluminum	<input type="text"/>
High Temp. Silicone Red	<input type="text"/>
White Latex Caulk	<input type="text"/>

### Directions for Submittal:

1. Fill out or circle appropriate information to ensure a timely return on your submittal quotation.
2. The more specific you can be on your assembly details and the quantity of products needed will help us determine the most appropriate and cost effective solution for your application.
3. Fax quotation to (336) 661-7969.
4. A job quotation will be returned to you with delivered pricing via fax within 24 hours of receipt of submittal.
5. Visit [www.firestoppingcaulk.com](http://www.firestoppingcaulk.com) or contact us at 1-800-638-3160 for product specifications and testing or additional technical or customer support.

Flame Tech Inc.  
5180 Indiana Avenue  
Winston-Salem, NC 27106  
PH: 1-800-638-3160 Fx: (336)-661-7969 [www.firestoppingcaulk.com](http://www.firestoppingcaulk.com)