

PUR FILL NF 12

STRAW DISPENSED INSULATING FOAM SEALANT

TECHNICAL DATA SHEET



Product Description

PUR FILL NF 12 is a self hardening, closed cell polyurethane foam which expands to seal cracks in a variety of building substrates. The straw dispensed design is perfect for filling hard to reach places with no need for a foam applicator gun or cleaner. Each can of **PUR FILL NF 12** delivers approximately 960 cubic inches of cured foam which is the equivalent to a 3/8" diameter bead 780 feet long. **PUR FILL NF 12** increases energy efficiency by stopping exchange around windows, doors, wall intrusions and sill plates. It is perfect for filling holes around pipes and ducts, reduces noise, controls radon, stops foundation leaks, seals out moisture and much more.

Application Procedures

A necessary ingredient for proper cure is moisture from the air, which can be augmented by light misting spray in dry conditions. **PUR FILL NF 12** has a useful temperature range from -40° F to 176° F, is tack free in 15 minutes and can be cut in 45 minutes.

1. Shake can before each use.
2. Thread actuator and dispensing tube lightly onto the valve on the top of the can.
3. Hold can with the valve down.
4. Point dispensing tube to work area and tilt the actuator to dispense foam.

Packaging

Part #:	Product Description	Case Qty
TP-NF 12	Insulating foam sealant	12 cans/ case

Safety Recommendations

Eye protection and protective gloves are recommended. In case of eye contact, wash thoroughly with water and seek medical advice. In case of contact with skin, wipe away with a dry cloth and wash with soap and water immediately. Do not use solvents on skin to remove cured foam and avoid prolonged breathing of vapors. Do not use near open flame. Keep out of reach from children!

Shelf Life and Storage

PUR FILL NF 12 has a 1 year shelf life from the date of purchase. Keep pressurized container away from children. Protect from direct sunlight, heat and temperatures in excess of 120° F. Do not puncture or destroy by burning.

Disclaimer

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.

Physical Properties

(Based on cure at 68° F relative humidity)

Color:	Yellow
Expanded Volume:	.6 Cu. Ft. /17 liters
Density:	1.4 – 1.6 lbs/cu ft
Cell Structure:	70%
Tack Free Time:	15 minutes
Shelf Life:	1 year
Flame Spread:	20
Smoke Development:	70
R-Factor:	5.0 per Inch

PRODUCT FEATURES

- Economical
- High Volume
- Saves Labor
- Easy Application
- Seals out Noise
- UL Listed



Flame Tech Inc.

5180 Indiana Avenue, Winston-Salem, NC 27106

Ph: 1-800-638-3160 Fx: 1-336-661-7969

www.firestopningcaulk.com