

PAINTERS PREFERRED

ACRYLIC LATEX CAULK TECHNICAL DATA SHEET



Product Description

Painters Preferred Acrylic Latex Caulk is a white, general purpose caulking material that applies with a smooth consistency and cures to a tough rubbery solid. **Painters Preferred Acrylic Latex Caulk** is an economical caulking material that is suitable for multiple interior/exterior applications such as sealing and bonding joints around wood, glass, aluminum and other surfaces. **Painters Preferred** is ideal for use as a filler compound for joints, crack, seams and holes associated with pre-painting applications for both interior and exterior applications.

Specifications

Painters Preferred Acrylic Latex Caulk meets ASTM-C834 performance specifications

Application Procedures

1. Clean surface free from oils, loose mortar, release agents, old caulking, old paint, or other contaminants.
2. Clip off tip of spout @ a 45 degree angle to desired size.
3. Apply using steady, even pressure to completely bridge joints.
4. Smooth caulk using wet finger or a damp cloth for a neat appearance.
5. Wipe away excess with a damp cloth before surface skins.
6. Allow a minimum of two hours dry time before painting with latex or oil based paint. Allow extra dry time during periods of high humidity and/or cool temperatures

Packaging

Part #:	Product Description	Color	Case Qty
KRY-WL30100	Painters Preferred 10 Fl. Oz. Tube	White	12 tubes/ case

Performance Data


Joint Movement Capability:	Low
Freeze-Thaw Stability:	Stable -5 cycles
Durability:	25 Years
Clean Up:	Warm water
Flexibility:	Good

Disclaimer

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.

Cautions: Contains Crystalline Silica. Use only with adequate ventilation. Avoid contact with eyes and skin. Wash hands after using. Do not transfer contents to other containers for storage. **KEEP OUT OF REACH OF CHILDREN**

PRODUCT FEATURES
➤ Meets ASTM C834
➤ Economical
➤ Applies Easily
➤ Smooth Consistency
➤ Excellent Adhesion
➤ Durable & Long Lasting
➤ Mildew Resistant
➤ Paintable
➤ Low V.O.C's



Physical Properties

Type:	Acrylic Latex Caulk
Color:	Bright White
Shelf Life:	12 months
Flash Point:	N/A Water Based
Flammability:	N/A Water Based
Cure Time:	7-14 days
Tack Free Time:	5 - 7 minutes
Application Temp:	50°F to 120°F
Service Temperature:	-30°F to 180°F
VOC Level:	.38 lb/gal
Mildew Resistance:	Good
Water Resistance:	Good
Odor:	Low/None
Shrinkage:	Low/Moderate
Solids by Weight:	82%
Weight/Gallon:	13.5 lbs/gal

Flame Tech Inc.

5180 Indiana Avenue, Winston-Salem, NC 27106

Ph: 1-800-638-3160 Fx: 1-336-661-7969

www.firestoppingcaulk.com

