

PRO VALUE

SLICONIZED ACRYLIC LATEX CAULK TECHNICAL DATA SHEET



Product Description

Pro Value Siliconized Acrylic Latex Caulk forms a long lasting thermal and moisture protective seal between most building materials including wood, masonry, concrete, brick, drywall, metal, and glass. It has excellent resistance to water, weathering, and moisture vapor. **Pro Value** is designed for interior and exterior use, is paintable, and is mildew resistant.

Specifications

Pro Value meets ASTM-C834 performance specifications

Application Procedures

1. Clean surface free from oils, loose mortar, release agents, old caulking, old paint, or other contaminants.
2. Clip off tip of spout @ a 45 degree angle to desired size.
3. Apply using steady, even pressure to completely bridge joints.
4. Smooth caulk using wet finger or a damp cloth for a neat appearance.
5. Wipe away excess with a damp cloth before surface skins.
6. Allow a minimum of two hours dry time before painting with latex or oil based paint. Allow extra dry time during periods of high humidity and/or cool temperatures

PRODUCT FEATURES

- Economical
- Applies Easily
- Smooth Consistency
- Excellent Adhesion
- Durable & Long Lasting
- Mildew Resistant
- Paintable
- Low V.O.C's
- Easy Clean-up

Packaging

Part #:	Product Description
KRY-WL0009650	Pro Value 10 Fl. Oz. Tube

Color	Case Qty
White	12 tubes/ case

Paintability

A minimum of 2 hours dry time is required before painting with latex or oil base paint. Allow extra dry time during periods of high humidity and/or cool temperatures.

Clean Up

Excess caulk should be cleaned off tools and nonporous surfaces while it is in the uncured state, using a wet cloth. Cured compounds should be cut away.

Disclaimer

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies are excluded. No other warranties apply, including fitness for a particular purpose.

KEEP OUT OF REACH OF CHILDREN

Physical Properties

Type:	Latex w/ Silicone
Colors:	Bright White
Shelf Life:	12 months
Flash Point:	N/A (Water based)
Flammability:	N/A (Water based)
Open Time:	< 10 minutes @ 75°F
Cure Time:	5-7 days at 75°F
Tack Free Time:	< 20 minutes @ 75°F
Application Temp. :	Above 40°F
Service Temperature:	-30°F to 180°F
Storage Temperature:	Above 32°F
VOC Level:	20 lbs/gal
Mildew Resistance:	Good
Water Resistance:	Good
Odor:	Low
Shrinkage:	Low/Moderate
Solids by Weight:	83.5 ± 1%
Weight/Gallon:	13.2 ± 0.2 lb.
Painting:	After 2 hours
Joint Movement Capability:	Good
Joint Size:	< 1/2" x 1/2"
Freeze-Thaw Stability:	5 cycles
Clean Up:	Water
Flexibility:	Excellent
Durability:	40 Years



Flame Tech Inc.

5180 Indiana Avenue, Winston-Salem, NC 27106

Ph: 1-800-638-3160 Fx: 1-336-661-7969

www.firestopincacaulk.com

